

Braçadeira roscada c/reforço


Clamp saddle with reinforce

Collier de prise en charge avec renfor


Collarine de toma con refuerzo





02 15 2000 000




d	G	L	H	DI x W	Paraf	PN/Bar	Gr	Quant	Nº Código
16	" 1/2	61	36	13,11x2,62	2 (M6x40)	10	61	B 70	02 15 2000 092
20	" 1/2	61	36	13,11x2,62	2 (M6x40)	10	61	C 200	02 15 2000 001
20	" 3/4	65	40	13,11x2,62	2 (M6x40)	10	72	C 200	02 15 2000 094
20	1 "	76	45	13,11x2,62	2 (M6x40)	10	85	C 200	02 15 2000 095
25	" 1/2	61	36	13,87x3,53	2 (M6x40)	10	62	C 200	02 15 2000 003
25	" 3/4	61	36	13,87x3,53	2 (M6x40)	10	70	C 180	02 15 2000 004
25	1 "	76	45	13,87x3,53	2 (M6x40)	10	84	C 150	02 15 2000 097
32	" 1/2	76	45	18,64x3,53	2 (M8x60)	10	130	C 100	02 15 2000 005
32	" 3/4	76	45	18,64x3,53	2 (M8x60)	10	125	C 100	02 15 2000 006
32	1 "	76	45	18,64x3,53	2 (M8x60)	10	146	C 100	02 15 2000 007
40	" 1/2	76	55	18,64x3,53	2 (M8x60)	10	134	C 100	02 15 2000 008
40	" 3/4	76	55	18,64x3,53	2 (M8x60)	10	143	C 100	02 15 2000 009
40	1 "	76	55	18,64x3,53	2 (M8x60)	10	140	C 90	02 15 2000 010



d	G	L	H		Paraf	PN/Bar	Gr	Quant	Nº Código
DI x W									
50	" 1/2	83	60	28,17x3,53	2 (M8x60)	10	150	C 80	02 15 2000 011
50	" 3/4	83	60	28,17x3,53	2 (M8x60)	10	158	C 80	02 15 2000 012
50	1 "	83	60	28,17x3,53	2 (M8x60)	10	160	C 70	02 15 2000 013
63	" 1/2	102	69	28,17x3,53	4 (M8x60)	10	255	C 50	02 15 2000 014
63	" 3/4	102	69	28,17x3,53	4 (M8x60)	10	257	C 50	02 15 2000 015
63	1 "	102	69	34,52x3,53	4 (M8x60)	10	273	C 50	02 15 2000 016
63	1" 1/4	102	69	40,87x3,53	4 (M8x60)	10	277	C 50	02 15 2000 017
63	1" 1/2	102	69	53,90x3,53	4 (M8x60)	10	299	C 45	02 15 2000 018
75	" 1/2	120	95	53,90x3,53	4 (M8x60)	10	355	C 30	02 15 2000 019
75	" 3/4	120	95	53,90x3,53	4 (M8x60)	10	358	C 30	02 15 2000 020
75	1 "	120	95	53,90x3,53	4 (M8x60)	10	368	C 30	02 15 2000 021
75	1" 1/4	120	95	53,90x3,53	4 (M8x60)	10	376	C 30	02 15 2000 022
75	1" 1/2	120	95	53,90x3,53	4 (M8x60)	10	381	C 30	02 15 2000 023
75	2"	120	95	53,90x3,53	4 (M8x60)	10	387	C 30	02 15 2000 089
90	" 1/2	132	115	53,90x3,53	6 (M8x60)	10	498	C 20	02 15 2000 024
90	" 3/4	132	115	53,90x3,53	6 (M8x60)	10	502	C 20	02 15 2000 025
90	1 "	132	115	53,90x3,53	6 (M8x60)	10	514	C 20	02 15 2000 026
90	1" 1/4	132	115	53,90x3,53	6 (M8x60)	10	523	C 20	02 15 2000 027
90	1" 1/2	132	115	53,90x3,53	6 (M8x60)	10	530	C 20	02 15 2000 028
90	2"	132	115	53,90x3,53	6 (M8x60)	10	542	C 16	02 15 2000 090



d	G	L	H		Paraf	PN/Bar	Gr	Quant	Nº Código
DI x W									
110	" 1/2	153	129	65,09x3,53	6 (M8x60)	10	622	C 12	02 15 2000 029
110	" 3/4	153	129	65,09x3,53	6 (M8x60)	10	628	C 12	02 15 2000 030
110	1 "	153	129	65,09x3,53	6 (M8x60)	10	628	C 12	02 15 2000 031
110	1" 1/4	153	129	65,09x3,53	6 (M8x60)	10	628	C 12	02 15 2000 032
110	1" 1/2	153	129	65,09x3,53	6 (M8x60)	10	648	C 12	02 15 2000 033
110	2 "	153	129	65,09x3,53	6 (M8x60)	10	648	C 12	02 15 2000 034
125	1"	176	130	63,09x3,53	6 (M8x60)	10	675	C 12	02 15 2000 036
125	1 "1/4	176	130	63,09x3,53	6 (M8x60)	10	680	C 12	02 15 2000 037
125	1 "1/2	176	130	63,09x3,53	6 (M8x60)	10	689	C 12	02 15 2000 038
125	2 "	176	130	63,09x3,53	6 (M8x60)	10	685	C 12	02 15 2000 039
140	1 "	192	135	53,90x3,53	6 (M8x60)	10	800	C 10	02 15 2000 041
140	1" 1/4	192	135	53,90x3,53	6 (M8x60)	10	803	C 10	02 15 2000 042
140	1" 1/2	192	135	53,90x3,53	6 (M8x60)	10	803	C 10	02 15 2000 043
140	2 "	192	135	53,90x3,53	6 (M8x60)	10	825	C 10	02 15 2000 044
140	2" 1/2	192	135	71,44x3,53	6 (M8x60)	6	830	C 8	02 15 2000 045
140	3 "	192	135	71,44x3,53	6 (M8x60)	6	837	C 8	02 15 2000 046
160	1 "	212	135	53,90x3,53	6 (M8x60)	10	874	C 8	02 15 2000 048
160	1" 1/4	212	135	53,90x3,53	6 (M8x60)	10	878	C 8	02 15 2000 049
160	1" 1/2	212	135	53,90x3,53	6 (M8x60)	10	881	C 8	02 15 2000 050
160	2 "	212	135	53,90x3,53	6 (M8x60)	10	891	C 8	02 15 2000 051
160	3 "	212	135	71,44x3,53	6 (M8x60)	6	925	C 8	02 15 2000 053



d	G	L	H		Paraf	PN/Bar	Gr	Quant	Nº Código
DI x W									
200	1 "	252	140	53,90x3,53	6 (M8x60)	10	1010	C 6	02 15 2000 055
200	1" 1/4	252	140	53,90x3,53	6 (M8x60)	10	1040	C 6	02 15 2000 056
200	1" 1/2	252	140	53,90x3,53	6 (M8x60)	10	1046	C 6	02 15 2000 057
200	2 "	252	140	53,90x3,53	6 (M8x60)	10	1063	C 6	02 15 2000 058
200	3 "	252	140	71,44x3,53	6 (M8x60)	6	1110	C 4	02 15 2000 060
225	1" 1/4	294	170	56,00x6,00	6 (M10x80)	6	1760	C 3	02 15 2000 062
225	1" 1/2	294	170	56,00x6,00	6 (M10x80)	6	1760	C 3	02 15 2000 063
225	2 "	294	170	64,00x6,00	6 (M10x80)	6	1780	C 3	02 15 2000 064
225	2" 1/2	294	170	70,00x6,00	6 (M10x80)	4	1790	C 3	02 15 2000 065
225	3 "	294	170	116,84x6,99	6 (M10x80)	4	1750	C 3	02 15 2000 066
225	4 "	294	170	116,84x6,99	6 (M10x80)	4	1830	C 3	02 15 2000 067
250	1" 1/4	320	180	56,00x6,00	6 (M10x80)	6	2090	C 2	02 15 2000 070
250	1" 1/2	320	180	56,00x6,00	6 (M10x80)	6	2090	C 2	02 15 2000 071
250	2 "	320	180	64,00x6,00	6 (M10x80)	6	2110	C 2	02 15 2000 072
250	2" 1/2	320	180	70,00x6,00	6 (M10x80)	4	2110	C 2	02 15 2000 073
250	3 "	320	180	116,84x6,99	6 (M10x80)	4	2130	C 2	02 15 2000 074
250	4 "	320	180	116,84x6,99	6 (M10x80)	4	2220	C 2	02 15 2000 075
315	1" 1/4	390	200	56,00x6,00	6 (M10x80)	6	2810	C 1	02 15 2000 080
315	1" 1/2	390	200	56,00x6,00	6 (M10x80)	6	2820	C 1	02 15 2000 081
315	2 "	390	200	64,00x6,00	6 (M10x80)	6	2830	C 1	02 15 2000 082
315	2" 1/2	390	200	70,00x6,00	6 (M10x80)	4	2840	C 1	02 15 2000 083
315	3 "	390	200	116,84x6,99	6 (M10x80)	4	2850	C 1	02 15 2000 084
315	4 "	390	200	116,84x6,99	6 (M10x80)	4	2880	C 1	02 15 2000 085